



Dial Depth Gauges

- Lock screw for dial bezel
- Lock screw for holding the measuring rod in position
- Optional base extensions of 7" and 12" (175 and 300 mm) are available to increase the base span on both models
- Removable hook attachment permits readings from the edge of a workpiece to edges of slots, shoulders, etc.



Range"	Description	Model No.	EDP No.	Price/Each
GRADUATION - .001"				
0-6	6" Gauge without Case	HU882	56766	
0-12	12" Gauge without Case	HU883	56768	
GRADUATION - 0.02 MM				
0-300 mm	300 mm Gauge without Case	HU885	64276	

ACCESSORIES

Description	Model No.	EDP No.	Price/Each
7"/175 mm Base Extension	HU888	65861	
12"/300 mm Base Extension	HU889	65862	
6" Case Only	HU886	56776	
12" Case Only	HU887	56777	

Steel Rule Depth Gauges

- Gauge can be smoothly adjusted to the required measurement and then locked into position by a knurled nut
- Base is cut out on one side, adjacent to the rule, permitting easier readings and more accurate measurements



Model No.	EDP No.	Graduation	Head Length x Width	Price /Each
0-6" RANGE				
HU238	51080	32nds, 64ths	2 5/8" x 1/8"	
0-150 MM RANGE				
HU239	51081	mm, 1/2 mm	66 x 3 mm	



Precision Universal Bevel Vernier Protractors

(WITH FINE ADJUSTMENT)

- Graduations in degrees through 360°
- Available with hardened 7" (175 mm) or 12" (300 mm) blades which can be rotated to the desired angle and adjusted to the desired length
- Both the dial and the blade can be locked independently
- An acute angle attachment is available
- Flush surfaces on the base permits use on height gauges
- One side of the tool is flat so it can be laid on paper or on the work



IN CASE

Blade Size	Graduation	Model No.	EDP No.	Price/Each
7" & 12"	5 min. or 1/12°	HU462	51398	
7" & 12"	5 min. or 1/12°	HU463*	66929	

ACCESSORIES

Description	Model No.	EDP No.	Price/Each
7" Blade Only	HU464	70538	
12" Blade Only	HU465	70539	
Acute Angle Attachment Only	HU466	51392	

* With standard letter of certification

Electronic Depth Gauges 3753A Series

- Linear accuracy: ± 0.001" (± 0.03 mm)
- Resolution: 0.0005" (0.01 mm)
- Inch/millimeter conversion
- Hardened stainless steel body and slide for long life
- Fine adjustment thumb roll for precision measurements
- Lock screw to hold the slide in position
- Zero at any position
- Hold readout at any position
- Limits button allows high and low limits to be set.
- Manual ON/OFF, plus a built-in automatic shut off
- Hardened base is standard 2 3/4" (70 mm) long, optional base extensions are available
- Included: Hook attachment and one 3 V battery no. CR2032 with one-year minimum life



Description	Model No.	EDP No.	Price /Each
0-6"/150 mm Range, Depth Gauge without Output, in Case	IA490	12258	
0-8"/200 mm Range, Depth Gauge without Output, in Case	IA634	12259	
0-12"/300 mm Range, Depth Gauge without Output, in Case	IA635	12260	

ACCESSORIES

Description	Model No.	EDP No.	Price/Each
7"/175 mm Base Extension	IA636	12261	
10.24"/260 mm Base Extension	IA637	12262	
12.6"/320 mm Base Extension	IA638	12262	
One 3 Volt Battery, No. CR2032	XC004	ECR2032BP	

Combination Steel Rule Depth & Angle Gauges

- The head is graduated both left and right to 30°, 45°, and 60°
- One side of the base is cut out to permit easier and more accurate readings
- The center of the head is recessed so that the tool will lay flat to permit more accurate measurements
- A tempered rule that has been accurately machined divided, is smoothly fitted to the head and can be locked in position by a knurled nut



0-6" RANGE

Graduation	Angle Degrees	Description	Model No.	EDP No.	Price /Each
		6" Combination gauge	HU233	51074	
		6" Combination gauge w/ hook rule	HU234	51075	
32nds, 64ths	30, 45, 60	6" Combination gauge w/ hook rule and rod	HU235	51076	
32nds, 64ths	None	6" Hook rule only	HU236	51077	
None	None	6" Rod only	HU237	51078	


Steel Protractors

- Double graduations from 0-180° in opposite directions permitting the direct reading of angles and supplementary angles
- The back of the tool is flat for ease of use
- The blade can be locked firmly at any angle by the lock nut
- Satin chrome finish for ease of reading and resistance to rust



Blade Length	Range	Model No.	EDP No.	Price/Each
6"	0-180°	HT283	50127	
6"	0-180°	HT847*	50672	

*Rectangular Head



Bevels

UNIVERSAL 6"/150 MM

Model No. HT408
EDP No. 50266
Price/Each \$

