

#### **Electronic Calipers**

- Lightweight, ergonomic design
- Large easy to read LCD, 32" high
- Inch/millimeter conversion reads 0.0005" or 0.01 mm
- Zero at any position
- Automatic shut off after 5 minutes of nonuse
- Single long life battery is easily accessible
- Hardened stainless steel body
- Integrated depth rod on all sizes
- Fine adjustment thumb wheel
- Lock screw to hold the slide in position
- Resolution is 0.0005" (0.01 mm)
- Furnished in a fitted protective case



| Model<br>No. | Mfg<br>No.   | Range          | Approximate<br>Jaw Depth                      | Price<br>/Each |
|--------------|--------------|----------------|---|----------------|
| IA386        | 799A-6/150   | 0-6" (0-150mm) | 1 1/2" (38 mm) Outside,<br>5/8" (16 mm)Inside |                |
| IA379        | EC799A-8/200 | 0-8" (0-200mm) | 2" (50.8 mm) Outside,<br>3/4" (19 mm) Inside  |                |

### **Extended Range Electronic Digital Calipers**

- Lightweight, ergonomic design
- Inch/millimeter conversion reads 0.0005" or 0.01 mm
- Hardened stainless measuring surfaces for long life
- Fine adjustment thumb wheel
- Lock screw to hold the slide in position
- Resolution: 0.0005" (0.01 mm)
- Zero at any position
- Preset and hold feature
- Minimum and maximum limits set
- LCD characters are 0.50" high
- Automatic shut-off after 30 minutes of non-use
- Last measuring position retained when shut off
- Includes: protective fitted case



| Model No. | Mfg. No.      | Description                                  | Price/Each |
|-----------|---------------|--|------------|
| IA473     | 799AZ-24/600  | Electronic Slide Caliper w/Case 24"/600 mm   |            |
| IA623     | 799AZ-40/1000 | Electronic Slide Caliper w/Case, 40"/1000 mm |            |

# **Dial Calipers**

- Sharp, clear dial graduations of 0.001" with 0.100" per revolution
- Thumb-operated fine adjustment roll
- Sharp, black graduations on the satin finished bar, every 0.100"
- Lock screws for sliding jaw and dial bezel
- Covered rack depth rod 6" and 8" models
- Knife-edge contacts
- Adjustable bezel
- Hardened stainless steel bar, measuring surfaces, rack, gears and depth rod
- Positive, spring-loaded double pinion anti-backlash control



| Model No. | Mfg. No. | Description             | Price/Each |
|-----------|----------|-------------------------|------------|
| HW273     | 1202-6   | 6" Dial Caliper w/Case  |            |
| HX214     | 1202-8   | 8" Dial Caliper w/Case  |            |
| HX215     | 3202-12  | 12" Dial Caliper w/Case |            |

### All Stainless Steel Electronic **Digital Calipers**

- Large LCD display provides easy-to-read numbers
- Precision adjustments for accurate measurements
- Hardened stainless steel head and body
- Lock screw to hold slide in position
- Linear accuracy: +/- .001" (.03 mm)
- Inch/millimeter conversion
- Zero at any position
- ON/OFF button
- Includes: Two 1.5 V batteries, type LR44 and deluxe storage case with foam inserts



| Model No. | Size | Measurement Range | Approximate Jaw Depth     | Price/Each |
|-----------|------|-------------------|---------------------------|------------|
| TGZ370    | 6    | 0-6" (152 mm)     | 1 9/16" (40 mm) outside,  | _          |
|           |      |                   | 13/16" (21 mm) inside     |            |
| TJZ861    | 8    | 0-8" (200 mm)     | 1 13/16" (46 mm) outside, |            |
|           |      |                   | 1" (26 mm) inside         |            |
| THZ769    | 12   | 0-12" (300 mm)    | 2 3/8" (60 mm) outside,   |            |
|           |      |                   | 1" (26 mm) inside         |            |

# **6" Electronic Digital Calipers**

- Large LCD display provides easy-to-read numbers
- Precision adjustments for accurate measurements
- ABS plastic head and stainless steel body
- Lock screw to hold slide in position
- Approximate jaw depth:
- 1 9/16" (40 mm) outside, 13/16" (21 mm) inside
- Inch/millimeter conversion
- Zero at any position
- Automatic shut OFF
- Includes two 3.0 V batteries, type CR3032 and a deluxe storage case with foam insert



| Model Measurement<br>No. Range |                 | Resolution      | Price<br>/Each |
|--------------------------------|-----------------|-----------------|----------------|
| TLV181                         | 0-6" (0-152 mm) | 0.001" (0.03mm) |                |

# ABS Digimatic Caliper

- Digital readout LCD shows inch or metric units for versatility when measuring
- Advanced onsite sensor (AOS) electromagnetic inductive sensor for resistance to dirt, oil, and water
- · Measures inside, outside, depth, and step values for versatility
- · Includes protective case and SR44 silver oxide battery



# Mitutoyo

| Model | Mfg.       | Measuring           | Resolution        | Accuracy           | Price |
|-------|------------|---------------------|-------------------|--------------------|-------|
| No.   | No.        | Range               |                   | +/-                | /Each |
| HM704 | 500-196-30 | 0"-6" (0 mm-152 mm) | 0.0005" (0.01 mm) | 0.001" (0.0254 mm) |       |