

Strapping Comparison

Performance Factor	Polypropylene	Polyester Cord	Steel
Break Strength	Good	Very Good	Excellent
Elongation*	20-25%	12-15%	2-4%
Ability to Retain Tension	Poor	Very Good	Excellent
Elongation Recovery	Excellent	Good	Poor
Split Resistance	Poor	Good	Excellent
Recyclability	Good	Good	Good
Cost	Least Expensive	More Expensive	Most Expensive

^{*}In the working range (40-60% of ultimate break strength).

Steel Strapping

- Strongest material for a wide range of strapping requirements
- Ideal for heavy shipments that require stronger protection over polypropylene and polyester
- Black painted and waxed finished
- Oscillated wound



Priced per Spool

Model No.	Core Dimensions"	Strap Width"	Strap Thickness"	Feet /Coil	Strength lbs.	Price /Each
PG001	16 x 3	3/8	0.015	5310	680	
PG002	16 x 3	3/8	0.020	3800	900	
PG003	16 x 3	1/2	0.015	3550	910	
PF404	16 x 3	1/2	0.020	2940	1200	
PG004	16 x 3	1/2	0.023	2370	1380	
PG005	16 x 3	5/8	0.015	2820	1125	
PF405	16 x 3	5/8	0.020	2360	1500	
PG006	16 x 3	5/8	0.023	1890	1725	
PG007	16 x 3	3/4	0.015	2385	1360	
PF406	16 x 3	3/4	0.020	1960	1800	
PG008	16 x 3	3/4	0.023	1580	2070	
PG515*	16 x 1-1/4	1-1/4	0.029	760	5500	
PF407*	16 x 1-1/4	1-1/4	0.031	760	5500	

^{*} Ribbon wound

Steel Seals

- All fully galvanized steel
- Open (snap-on) type: Used on flat and smooth surfaces
- Fully closed (push) type: Used on curved and irregular surfaces



	•
-	
	THE WILDS

		Price	ed per Box			Price	d pe
Model No.	Strap Width"	Qty /Box	Price /Each	Model No.	Strap Width"	Qty /Box	
PEN S	SEALS (SNA	P-ON)		FULLY	CLOSED (P	USH)	
PF408	1/2	2000		PF415	1/2	2000	
PF409	5/8	2000		PF416	5/8	2000	
PF410	3/4	2000		PF417	3/4	2000	
PF411	1/2	5000		PF418	1/2	5000	
PF412	5/8	5000		PF419	5/8	5000	
PF413	3/4	5000		PF420	3/4	5000	
PF414	1 1/4	1000		PF421	1 1/4	1000	

Safety Cutters for Steel Strapping

STANDARD DUTY

Cuts steel strapping 3/8-1 1/4" wide x 0.036" thick

Safety design holds strapping in place to prevent injuries from flying ends

Rubber pads gently release strapping when being cut

Model No. PC446 Price/Each \$

HEAVY-DUTY

- Cuts steel strapping 3/8-2" wide x 0.050" thick
- Powerful drop-forged steel design
- Heavy-duty performance for industrial applications
- 24" long

1154

Model No. PC479 Price/Each \$





Steel Strapping Sealers

FOR USE WITH OPEN SEALS

- Double notch creates a strong interlocking joint
- Heat-treated steel construction for added durability
- Ball handles provide a superior grip
- · Ideal for use with feed-wheel tensioners

Model No.	Width"	Strap Thickness"	Price/Eac
PA550	1/2	0.018 - 0.023	
PA562	5/8	0.018 - 0.023	
PA551	3/4	0.018 - 0.027	



FOR USE WITH CLOSED & SEMI-CLOSED SEALS

- Single notch for use with closed and semi-closed seals
- Chrome-plated steel construction
- Ball handles provide a superior grip
- · Ideal for use with push-bar style tensioners

Model No.	Width"	Strap Thickness"	Price/Eac
PE351	1/2	0.018 - 0.023	
PE352	5/8	0.018 - 0.023	
PE353	3/4	0.018 - 0.027	



HEAVY-DUTY STEEL STRAPPING SEALER

- Single notch
- Heat-treated steel construction for added durability
- · Ideal for use with push-bar style tensioners
- For use with 1 1/4" wide steel strapping
- 28" long
- Accepts steel strapping between 0.025" to 0.035" thick

Model No. PB016 Closed & Semi-Closed Seals Price/Each \$

Model No. PF687 Open Seals Price/Each \$



Steel Strapping Tensioners

PUSH BAR STYLE

- Accepts steel strapping 0.020" thick
- Light tension
- Limited take-up
- Ideal for applications on small, round or irregular surfaces

FEED-WHEEL STYLE

- Accepts steel strapping 0.035" thick
- Fast and easy operation
- Medium/heavy tension
- Unlimited take-up
- Ideal for applications on flat surfaces



Model No.	Description	Width"	Price/Each	Model No.	Description
PA567	Standard	3/8 - 1/2		PC938	Standard
PE350	Heavy-Duty	3/8 - 3/4		PC399	Heavy-Dut

Model No.	Description	Width"	Price/Each
PC938	Standard	3/8 - 3/4	
PC399	Heavy-Duty	3/4 - 1 1/4	

Push Bar Style Steel Strapping Tensioners

- Accepts steel strapping 0.020" thick
- Light tension
- Limited take-up
- ideal for applications on small, round or irregular surfaces



		-		
Model			Use	Price
No.	Description	Width"	With	/Each
PC428	Heavy-Duty	1 1/4	Closed Seal	

www.tenaquip.com

