

Saf-T-Lok Bars

- Designed for economy and ease of operation
- Constructed with high strength industrial round tubing Easy to close and lock with its heavy-duty steel rack,
- handle and cast aluminum housing Replaceable molded pivoting rubber feet,
- 2" x 4" that grip firmly to trailer walls Easy to open trigger release

KINEDYNE The Cargo Control People!™

Mfg.

10085

10088

10096

Logistic Tracks

No.

- Adjusts from 90" to 105"

Model

ND698

KH574

KH575

No.

- Optional cargo hoop set, two hoops, which bolts quickly and easily to provide greater area of holding surfaces (installation hardware included)
- Available in either steel or aluminum versions
- Extra long steel version is available upon request

Description

Steel Saf-T-Lok Bar

Aluminum Saf-T-Lok Bar

Cargo Hoop Set



Designed to hold securely in place

Jack Bars

- Constructed with high strength industrial square tubing Patented quick-release handle assembly which allows the
- operator to quickly adjust the length of the bar
- Durable jacking mechanism that securely hold the bar in place Replaceable molded pivoting 4" x 4"
- rubber feet, that grip firmly to trailer walls Adjusts from 86" to 114"
- Galvanized finish



	0	*		
Model	Mfg		Wt.	Price
No.	No.	Descr	iption Ibs.	/Each
PE108	JB101XL	Square One	Piece Jack Bar 17.2	

Aluminum Decking/Shoring Beams

For 96" and 102" trailers

The Cargo Control People!

KINEDYNE

- Made from extruded high strength aluminum
- Designed to give maximum strength at the least possible weight Keyhole slot allows the beams to be hung and stored in the
- trailer out of the way when they are not in use
- Decking/Vertical Rating: 2200 lbs. uniformly distributed working load limit
- Head assemblies are all steel, zinc-plated and tapered for ease of operation
- Shoring/Horizontal Rating: 2000 lbs. uniformly distributed working load limit
- Note: Working load limits are 1/3 of the ultimate breaking strength.

Model No. ND360 Mfg. No. FE8066-3

Price/Each \$

KINEDYNE The Cargo Control People!



Chains

Kinedyne[®] allows consumers to buy chain pre-cut and assembled with grab hook in an "Easy to Carry - Easy to Store Box"

- All Chain is Transportation Grade 70
- Precut to either 16, 20 or 25 foot lengths
- Comes fully assembled with
- installed grab hooks
- Gold dichromate finish
- All markings & ratings are compliant with the National Association of Chain Manufacturers (NACM)



KINEDYNE[®] The Cargo Control People!

Model	Mfg.		Chain	Working Load Limit		Price
No.	No.	Length'	Size"	lbs.	kg	/Each
PE963	10034-16BX	16	5/16	4700	2135	
PE964	10034-20BX	20	5/16	4700	2135	
PE965	10034-25BX	25	5/16	4700	2135	
PE966	10038-16BX	16	3/8	6600	3000	
PE967	10038-20BX	20	3/8	6600	3000	
PE968	10038-25BX	25	3/8	6600	3000	



Warning:

Rope Tie-Offs

- Made with 2" wide 4900G webbing and include 1-27 D-Ring hardware
- Are tagged to comply with North America Cargo
- Securement Standards Working Load Limit: 1,000 lbs.
- Fitting Length: 6"

Model No. PG110 Mfg. No. 660001 Price/Each \$

Corner Protectors

- from damage caused by the load Steel protectors feature a corner
- Material: Steel Length: 5"
- Width 5
- Model No. PG096 Mfg. No. 1863 Price/Each \$

Model No. PG097 Mfg. No. 1865 Price/Each \$





KH575

Price

/Each

KH574

Wt.

lbs.

11.4

8.5

13.3