



ProPolymer® Flashlights

- Waterproof, non-conductive polymer casings
- Easy to use push button momentary or constant "on-off" switching
- XC054** features super bright, 100000 hour lifetime LEDs
- XC056** contains a super high flux LED with a 10000 hour lifetime
- XC054** and **XC056** include batteries
- XC054** are CUL Listed Class I, II, Div. 2, Class III and MSHA approved
- XD467** is CUL Listed for Class I, II, Div. 1, Class III and MSHA approved
- XC056** is CUL Listed for Class I, II, Div. 2, Class III
- XD436**: Intrinsic Safety for Haz. Loc. Class I, II, Div. 1, Groups A,B,C,D,E,F,G; Class III, T4A



Model No.	Mfg. No.	Description	Lumens	Price /Each
XC054*	68202	4 AA LED, 155 Hours of Continuous Run Time	67	
XC056*	68244	4 AA Lux LED, Div. 2, 4 Hours with 2 Additional Hours of Declining Usable Light	100	
XD436	62202	3 "N" Size Alkaline, LED, 120 Hours of Continuous Run Time	30	
XD467*	67101	2 AA LED, HAZ-LO®, 24 Hours of Continuous Run Time	65	

* Batteries included

Survivor®

- Brightest right-angle LED flashlight available
- Features a C4® LED with a 405 m. range and optimal peripheral illumination
- LED produces up to 175 lumens and has a 50000 hour lifetime
- Raised push button switch features: High, Low, Flash and moonlight
- Run time (rechargeable): **High** 3.5 hours; **Low** 13 hours; **Flash** 5 hours; **Moonlight** 20 days
- Run time (alkaline): **High** 4 hours; **Low** 15 hours; **Flash** 8 hours; **Moonlight** 20 days
- Constructed of high-impact, super-tough nylon for durability and O-ring sealed for water-resistance
- Unbreakable polycarbonate lens with silicone anti-scratch coating
- Rechargeable models also include alkaline battery pack (alkaline batteries not included)
- Operates on 4 AA alkaline or rechargeable NiMH battery pack
- Serialized for easy identification
- UL Approved for Class I, Div. 1, Groups C, D; Class I, Div. 2, Groups A, B, C, D; Class II Div. 11, Groups F, G, Class III, T4, MSHA alkaline only



Model No.	Mfg. No.	Description	Lumens		Colour	Price /Each
			High	Low		
XC400	90513	Survivor® Rechargeable	175	60	Yellow	
XC401	90503	Survivor® Rechargeable	175	60	Orange	
XC402	90540	Survivor® Alkaline	175	60	Orange	
XC403	90541	Survivor® Alkaline	175	60	Yellow	
XC405	90542	Alkaline Battery Pack (Batteries Not Included)	-	-	-	

Knucklehead® Spot LED Flashlights

- Shockproof C4® premium LED technology
- Deep dish parabolic reflector produces a focused beam for longer distances: 210 m on high beam
- Durable spring-loaded clip for easy attachment to turnout gear and uneven surfaces
- Features a 210° articulating head that rotates a full 360°
- Four modes:
 - High:** 11 000-candela peak beam intensity, 180 lumens, 3.5-hour runtime
 - Low:** 3300-candela peak beam intensity, 55 lumens, 16-hour runtime
 - Moonlight:** 20-day runtime
 - Flash:** 8-hour runtime
- Dual power source: accepts rechargeable NiCad battery pack or four AA alkaline batteries
- Rubber dome push-button actuator is easy to operate even when wearing heavy gloves
- Removable magnet with 135-lb. pull strength features a replaceable rubber boot
- Optimized electronics provide regulated intensity
- High-impact, super-tough nylon polymer construction for exceptional durability
- 2-m impact-resistance tested
- IPX4-rated for water-resistance



Model No.	Mfg. No.	Description	Lumens	Price /Each
XD010	90757	Knucklehead® Spot 120 V AC/12 V DC, Orange	180	
XC405	90542	Alkaline Battery Pack (Batteries Not Included)	-	
XB872	EN91	Replacement Alkaline Batteries, AA, 24/Pkg.	-	/Pkg.

Knucklehead® Flood LED Flashlights

- High-impact super-tough nylon offering exceptional durability
- Super-bright C4® LED is impervious to shock and has a 50000 hour lifetime
- IPX4-rated for water resistant operations
- All openings O-ring sealed
- Full 360° rotation head with 210° of articulation
- Removable magnet with 135-lb. pull strength and integrated hook
- Lens is an unbreakable polycarbonate with silicone anti-scratch coating and is assembled in a heavy-duty bezel
- XD862:** AC/DC - Class I, Div. 1 approved for hazardous locations
- XD863:** Class I, Div. 1 approved for hazardous locations
- XD863** includes 4 AA alkaline batteries
- Charger meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position



Model No.	Mfg. No.	Battery	Lumens	Price /Each
XC766	90627	Industrial Rechargeable NiMH 4.8 V Can be Charged Up to 1000 Times	200	
XC767	90642	4 AA Alkaline Non-Rechargeable Battery Pack	200	
XD862	91627	HAZ-LO® Rechargeable Worklight	163	
XD863	91642	HAZ-LO® Worklight	163	